

NNo.

Nylon Mesh (Monofilament)

品番 Fabric No.	糸種 6PA/66PA		組織 Type of weave	オープニング Mesh opening	開口率 Opening area	密度 Mesh count		線径 Diameter	紗厚 Thickness	製品幅および在庫 Available width		
						/cm	/inch			cm	102-108	112-114
			inch	42	45							
NNo.20T	6		PW	970	58	8	20	300	555		●	
NNo.30T	6		PW	547	42	12	30	300	430		●	
NNo.35-250	6		PW	476	43	14	35	250	440		●	
NNo.40T	6		PW	435	47	16	40	200	377		●	
NNo.40HD	6		PW	400	40	16	40	235	435		●	
NNo.50HD	6	66	PW	308	37	20	50	200	350		●	
NNo.60HD	6		PW	263	39	24	60	160	289		●	
NNo.70T	6		PW	233	41	27	70	130	240		△	
NNo.70HD	6		PW	218	36	27	70	145	260			
NNo.80T	6		PW	213	45	31	80	105	200			
NNo.80HD	6	66	PW	188	35	31	80	130	231			●
NNo.90T		66	PW	177	39	35	90	105	195			
NNo.90HD	6		PW	152	29	35	90	130	226			
NNo.100M		66	PW	183	52	39	100	71	124			●
NNo.100HD		66	PW	149	34	39	100	105	188			●
NNo.110M		66	PW	160	48	43	110	71	120			●
NNo.110T		66	PW	152	43	43	110	79	135			
NNo.125T		66	PW	132	42	49	125	71	123			●
NNo.125HD		66	PW	124	37	49	125	79	135			△
NNo.150T		66	PW	108	41	59	150	61	104			●
NNo.150HD		66	PW	98	34	59	150	71	119			●
NNo.180M		66	PW	91	42	71	180	50	84			●
NNo.200T		66	PW	77	37	79	200	50	81			●
NNo.225T		66	PW	70	38	90	225	43	73			△
NNo.225HD		66	PW	63	31	90	225	50	85			
NNo.250T		66	PW	59	33	100	250	43	71			●
NNo.270T		66	PW	55	34	106	270	39	63			●
NNo.300-35		66	PW	50	35	120	300	35	58			●
NNo.300T		66	PW	46	29	120	300	39	64			●
NNo.330M		66	TW	42	30	130	330	35	69			●
NNo.350S		66	PW	43	35	140	350	30	47			●
NNo.350M		66	PW	38	27	140	350	35	58			●
NNo.380S		66	PW	37	30	150	380	30	49			●
NNo.380T		66	TW	32	23	150	380	35	60			●
NNo.420S		66	PW	30	25	165	420	30	48			●
NNo.420M		66	TW	25	17	165	420	35	68			●
NNo.508S		66	TW	20	16	200	508	30	57			●

* NNo.20T~180Mは「50m乱尺」、NNo.200T~508Sは「30m乱尺」となります。

* Approx.50m per roll for NNo.20T to 180M. Approx.30m per roll for NNo.200T to 508S.

- 製品幅（生産対応状況）
 - = 通常生産品（実績に基づいて生産しておりますが、将来の供給体制を保障するものではありません。）
 - 空欄 = 受注生産品
 - △ = 受注生産品ではありますが、在庫がある場合もございます。（要相談）
- オープニング・オープニングエリアはメッシュ数・線径に基づく計算値となっております。
- 組織はPW=平織、TW=綾織を表しております。
- 本規格は規格値であり、保証値ではありません。
- 本規格は改良などのために予告なく変更する場合がありますので、予めご了承ください。

- Available width (status of production availability)
 - = Regular product (Products are manufactured based on past records, but this does not guarantee future manufacturing conditions.)
 - Blank = Ordered product
 - △ = Ordered product, but may be available depending on stock levels. (Please feel free to contact us)
- Calculations of the mesh opening and opening area are based on the number of mesh and the diameter.
- Type of weave indicates PW=plain weaving and TW=twill weaving.
- The specifications are standard values and not guaranteed values.
- Please note that these specifications are subject to change without prior notice for improvements.