

TNo.

Polyester Mesh (Monofilament)

品番 Fabric No.	組織 Type of weave	オープニング Mesh opening	開口率 Opening area	密度 Mesh count		線径 Diameter	紗厚 Thickness	製品幅および在庫 Available width			
				/cm	/inch			cm	115	135	165
								inch	45	53	65
TNo.10T	PW	2040	65	4	10	500	946				
TNo.15T	PW	1293	58	6	15	400	776				
TNo.15HD	PW	1193	50	6	15	500	950				
TNo.20T	PW	970	58	8	20	300	560				
TNo.25S	PW	766	57	10	25	250	484	●	●	●	
TNo.25T	PW	716	50	10	25	300	560				
TNo.30T	PW	597	50	12	30	250	495	●			
TNo.36SS	PW	606	74	14	36	100	173			●	●
TNo.36T	PW	456	42	14	36	250	485				
TNo.40T	PW	435	47	16	40	200	377	●			●
TNo.50SS	PW	437	74	20	50	71	119	●	●	●	
TNo.50T	PW	363	51	20	50	145	265				
TNo.50HD	PW	308	37	20	50	200	353	●			
TNo.53T	PW	334	49	21	53	145	258				●
TNo.60-48	PW	375	79	24	60	48	85			●	
TNo.60SS	PW	369	76	24	60	54	90	●	●	●	
TNo.60-64	PW	359	72	24	60	64	106	●	●	●	
TNo.60S	PW	352	69	24	60	71	116	●			
TNo.60T	PW	303	51	24	60	120	201	●			●
TNo.60HD	PW	278	43	24	60	145	258	●	●	●	
TNo.70-48	PW	315	75	27	70	48	83			●	
TNo.70SS	PW	309	72	27	70	54	90	●	●	●	
TNo.70S	PW	292	65	27	70	71	115	●	●	●	
TNo.70T	PW	243	45	27	70	120	196				●
TNo.70HD	PW	218	36	27	70	145	260				
TNo.74T	PW	223	42	29	74	120	201	●	●	●	
TNo.80-48	PW	270	72	31	80	48	80			●	
TNo.80SS	PW	264	69	31	80	54	88	●	●	●	
TNo.80S	PW	247	60	31	80	71	116	●	●	●	
TNo.80T	PW	218	47	31	80	100	168	●	●	●	
TNo.86T	PW	195	44	34	86	100	165	●	●	●	
TNo.90-48	PW	234	69	35	90	48	84				
TNo.90SS	PW	228	65	35	90	54	88	●	●	●	
TNo.90S	PW	211	56	35	90	71	112	●			●
TNo.90T	PW	182	42	35	90	100	165				
TNo.100SS	PW	206	66	39	100	48	80	●	●	●	
TNo.100S	PW	200	62	39	100	54	87	●	●	●	
TNo.100M	PW	183	52	39	100	71	111	●	●	●	
TNo.100T	PW	174	47	39	100	80	132	●	●	●	
TNo.110T	PW	160	48	43	110	71	116	●	●	●	
TNo.110HD	PW	151	43	43	110	80	134	●	●	●	
TNo.120S	PW	164	60	47	120	48	79	●	●	●	
TNo.120M	PW	158	56	47	120	54	86	●	●	●	
TNo.120-64	PW	148	49	47	120	64	103			●	●
TNo.120HD	PW	132	39	47	120	80	130				●
TNo.125T	PW	132	42	49	125	71	125	●	●	●	
TNo.135S	PW	140	55	53	135	48	78	●	●	●	
TNo.135T	PW	134	51	53	135	54	85	●	●	●	
TNo.135-64	PW	124	44	53	135	64	102				●
TNo.135HD	PW	117	39	53	135	71	123				

* TNo.10T~180Tは「50m乱尺」、TNo.200-45~460Sは「30m乱尺」となります。

* Approx.50m per roll for TNo.10T to 180T. Approx.30m per roll for TNo.200-45 to 460S.

■ 製品幅 (生産対応状況)

● = 通常生産品 (実績に基づいて生産しておりますが、将来の供給体制を保障するものではありません。)

空欄 = 受注生産品 (品番によっては在庫がある場合がありますので、お気軽にお問い合わせください。)

■ オープニング・オープニングエリアはメッシュ数・線径に基づき計算値となっております。

■ 組織はPW=平織、TW=綾織を表しております。

■ 本規格は規格値であり、保証値ではありません。

■ 本規格は改良などのために予告なく変更する場合がありますので、予めご了承ください。

■ Available width (status of production availability)

● = Regular product (Products are manufactured based on past records, but this does not guarantee future manufacturing conditions.)

Blank = Ordered product (Some products may be available. Please feel free to contact us.)

■ Calculations of the mesh opening and opening area are based on the number of mesh and the diameter.

■ Type of weave indicates PW=plain weaving and TW=twill weaving.

■ The specifications are standard values and not guaranteed values.

■ Please note that these specifications are subject to change without prior notice for improvements.

品番 Fabric No.	組織 Type of weave	オープニング Mesh opening	開口率 Opening area	密度 Mesh count		線径 Diameter	紗厚 Thickness	製品幅および在庫 Available width			
				/cm	/inch			cm	115	135	160
								inch	45	53	63
TNo.150S	PW	121	51	59	150	48	77		●	●	●
TNo.150T	PW	115	46	59	150	54	84		●	●	●
TNo.150HD	PW	98	34	59	150	71	111				
TNo.160S	PW	111	49	63	160	48	79				●
TNo.160T	PW	105	44	63	160	54	83			●	●
TNo.160-64	PW	95	36	63	160	64	102	●	●	●	
TNo.160HD	PW	88	31	63	160	71	113				
TNo.180S	PW	93	44	71	180	48	74		●	●	●
TNo.180T	PW	87	38	71	180	54	83		●	●	●
TNo.200-45	PW	82	42	79	200	45	68				
TNo.200S	PW	79	39	79	200	48	73		●	●	●
TNo.200T	PW	73	33	79	200	54	82		●	●	●
TNo.225S	PW	73	42	90	225	40	59		●	●	●
TNo.225-45	PW	68	36	90	225	45	66				
TNo.225T	PW	65	33	90	225	48	72		●	●	●
TNo.225HD	PW	59	27	90	225	54	84		●	●	●
TNo.225HD	TW	59	27	90	225	54	93		●	●	●
TNo.250T	PW	62	37	100	250	40	59		●	●	●
TNo.270T	PW	60	41	106	270	34	51		●	●	●
TNo.270HD	PW	54	33	106	270	40	59				●
TNo.280T	PW	57	39	110	280	34	51		●	●	●
TNo.300S	PW	51	36	120	300	34	51		●	●	●
TNo.300T	PW	48	32	120	300	40/34	57		●	●	●
TNo.300HD	PW	45	28	120	300	40	61		●		●
TNo.310S	PW	52	40	122	310	30	45		●	●	●
TNo.330S	PW	47	37	130	330	30	45		●	●	●
TNo.330T	TW	43	31	130	330	34	60				●
TNo.350S	PW	43	35	140	350	30	45		●	●	●
TNo.350T	PW	39	29	140	350	34	54				●
TNo.350T	TW	39	29	140	350	34	59		●		●
TNo.380S	PW	37	30	150	380	30	45		●	●	●
TNo.380T	PW	33	24	150	380	34	58				
TNo.420S	PW	33	30	165	420	27	40		●	●	●
TNo.420M	PW	30	25	165	420	30	45				●
TNo.460S	PW	28	26	180	460	27	43				●

* TNo.10T~180Tは「50m乱尺」、TNo.200-45~460Sは「30m乱尺」となります。

* Approx.50m per roll for TNo.10T to 180T. Approx.30m per roll for TNo.200-45 to 460S.

■ 製品幅 (生産対応状況)

● = 通常生産品 (実績に基づいて生産しておりますが、将来の供給体制を保障するものではありません。)

空欄 = 受注生産品 (品番によっては在庫がある場合がありますので、お気軽にお問い合わせください。)

■ オープニング・オープニングエリアはメッシュ数・線径に基づく計算値となっております。

■ 組織はPW=平織、TW=綾織を表しております。

■ 本規格は規格値であり、保証値ではありません。

■ 本規格は改良などのために予告なく変更する場合がありますので、予めご了承ください。

■ Available width (status of production availability)

● = Regular product (Products are manufactured based on past records, but this does not guarantee future manufacturing conditions.)

Blank = Ordered product (Some products may be available. Please feel free to contact us.)

■ Calculations of the mesh opening and opening area are based on the number of mesh and the diameter.

■ Type of weave indicates PW=plain weaving and TW=twill weaving.

■ The specifications are standard values and not guaranteed values.

■ Please note that these specifications are subject to change without prior notice for improvements.