

Fabric No.	Type of weave	Mesh count		Diameter μm	Mesh opening μm	Opening area %	Thickness μm	Ink volume cm ³ /m ²	Available width			
		/cm	/inch						cm inch	115 45	135 53	155 61
150S	PW	59	150	48	121	51	76	39			●	●
180S	PW	71	180	48	93	44	75	33		●	●	●
200S	PW	79	200	48	79	39	74	29		●	●	●
225S	PW	90	225	40	73	42	63	26		●	●	●
225T	PW	90	225	48	65	33	73	24		●	●	●
250T	PW	100	250	40	62	37	61	23		●	●	●
270T	PW	106	270	34	60	41	54	22		●	●	●
270HD	PW	106	270	40	54	33	61	20				●
280T	PW	110	280	34	57	39	54	21		●	●	●
300S	PW	120	300	34	51	36	54	19		●	●	●
310S	PW	122	310	30	52	40	47	19				●
330S	PW	130	330	30	47	37	47	17				●
350S	PW	140	350	30	43	35	47	16		●	●	●
380S	PW	150	380	30	37	30	47	14				●
420S	PW	165	420	26	34	32	42	13		●		●

■ Available width (status of production availability)

- =Regular product (Products are manufactured based on past records, but this does not guarantee future manufacturing conditions.)

Blank=Ordered product (Some products may be available. Please feel free to contact us.)

- Calculations of the mesh opening, opening area, and ink volume are based on the number of mesh and the diameter.

■ Type of weave indicates PW=plain weaving and TW=twill weaving.

- The specifications are standard values and not guaranteed values.

- Please note that these specifications are subject to change without prior notice for improvements.