

品番 Fabric No.	組織 Type of weave	密度 Mesh count		線径 Diameter	オープニング Mesh opening	開口率 Opening area	紗厚 Thickness	インク容積 Ink volume	製品幅 Available width								
		/cm	/inch						μm	μm	%	μm	cm <sup>3</sup> /m <sup>2</sup>	cm	115	135	155
														inch	45	53	61
150S	PW	59	150	48	121	51	76	39			●	●					
180S	PW	71	180	48	93	44	75	33		●	●	●					
200S	PW	79	200	48	79	39	74	29		●	●	●					
225S	PW	90	225	40	73	42	63	26		●	●	●					
225T	PW	90	225	48	65	33	73	24		●	●	●					
250T	PW	100	250	40	62	37	61	23		●	●	●					
270T	PW	106	270	34	60	41	54	22		●	●	●					
270HD	PW	106	270	40	54	33	61	20				●					
280T	PW	110	280	34	57	39	54	21		●	●	●					
300S	PW	120	300	34	51	36	54	19		●	●	●					
310S	PW	122	310	30	52	40	47	19				●					
330S	PW	130	330	30	47	37	47	18				●					
350S	PW	140	350	30	43	35	47	16		●	●	●					
380S	PW	150	380	30	37	30	47	14				●					
420S	PW	165	420	26	34	32	42	13		●		●					

■ 製品幅 (生産対応状況)

- = 通常生産品 (実績に基づいて生産しておりますが、将来の供給体制を保証するものではありません。)
- 空欄 = 受注生産品 (品番によっては在庫がある場合がありますので、お気軽にお問い合わせください。)
- オープニング・オープニングエリア・インク容積はメッシュ数・線径に基づく計算値となっております。
- 組織はPW=平織、TW=綾織を表しております。
- 本規格は規格値であり、保証値ではありません。
- 本規格は改良などのために予告なく変更する場合がありますので、予めご了承ください。

■ Available width (status of production availability)

- = Regular product (Products are manufactured based on past records, but this does not guarantee future manufacturing conditions.)
- Blank = Ordered product (Some products may be available. Please feel free to contact us.)
- Calculations of the mesh opening, opening area, and ink volume are based on the number of mesh and the diameter.
- Type of weave indicates PW=plain weaving and TW=twill weaving.
- The specifications are standard values and not guaranteed values.
- Please note that these specifications are subject to change without prior notice for improvements.